

## VET-DOP, MODEL BF-1 SPECIFICATIONS

TYPE: CW Doppler blood flow detector

CONSTRUCTION: high impact ABS plastic with aluminum front and back panels

DOPPLER FREQUENCY: 9.4 MHz.

POWER: 4.5 VDC, 110mA

POWER SUPPLY: 3 ea. 1.5 volt, "C" cell alkaline batteries

DOPPLER FREQUENCY: 9.4 MHz.

CABLE/CONNECTOR: 5 Ft x 0.125" DIA. Cable/ molded 5 pin circular DIN connector

BATTERY LIFE: 50 hours

DIMENSIONS (OVERALL): Width: 7", Depth: 5", Height: 3"

WEIGHT (WITH BATTERIES): 24.6 oz.

FRONT PANEL CONTROLS/LAYOUT

Power switch: Press ON, Press OFF

Volume Control: Rotary potentiometer

Phone jack: 3.5 mm with speaker by-pass

Low battery indicator: Red LED

Speaker: 2.625" Alnico

BACK PANEL INPUT: Doppler circular DIN receptacle

BLOOD PRESSURE ACCESSORIES

Sphygmomanometer: Bulb with certified manometer and screw deflation valve. 0-300 mm Hg

Headset: Stereo audio headset with standard 3.5 mm plug

BP Cuff set: 5 ea, 2.5 cm, 3 cm, 5 cm, 6 cm and 7 cm width

tg.